

Product Description

The MEMtronics PSP03 miniature channel filter is designed to be a surface-mountable, high-performance fixed-frequency bandpass filter that supports channel selection and interference mitigation in the upper 5G bands.

The design utilizes dielectrically-loaded propagating waveguide cavities built with unibody construction for the ultimate in low loss with a small form factor. The filter is constructed from fused silica for ultra-stable operation over temperature.

This K-band filter provides a 5-pole filter function centered at 28.308 GHz with 425 MHz (1.5% bandwidth), exhibiting a nominal 2.3 dB insertion loss and a minimum 16 dB return loss over the passband. Rejection is > 20 dB at frequencies below 27.883 GHz and above 28.733 GHz, with an ultimate rejection of > 60 dB from 1 GHz thru 40 GHz.

This filter performance is provided as a demonstration of capabilities. Custom filters to meet specific user requirements are possible from 2 GHz-50 GHz, with passband bandwidths ranging from 0.5%-20%, with 2-12+ poles of filtering.

Primary Applications

- 5G channel selection
- Interference mitigation
- Improve frequency reuse



Key Features and Performance

- Passband: 28.095-28.52 GHz
- Nom. mid-band loss: 2.3 dB
- Rejection: > 20 dB Fc +/- 425 MHz
- > 60 dB 1-40 GHz
- Temp Range: -55°C to +105°C
- Chip dimensions: (< 0.01 in³)
0.830 x 0.175 x 0.060 inches
- Weight: 0.32 grams
- Surface mount, CPW interconnect

PSP03 Filter Performance

